


IRON GATE/DOOR





Mission

Let the world use the happiness windows and doors of WANJIA


BRAND INTRODUCTION

Foshan Wanjia Window and Door Co., Ltd has been established since 2012, which was located in Nanhai District, Foshan City, Guangdong Province, integrating R&D, design, production and manufacturing all in one. We mainly produce aluminum windows & doors, UPVC windows & doors, garage doors, wooden doors, iron doors, curtain wall, handrails & fences, sunrooms and so on. So far, WANJIA owns a large production base and an international operations center, with a total construction area of about 538,195 sq.ft. What's more, WANJIA have exported products to more than 150 countries and regions. We aim to creative more extraordinary window and door product collections in the globe. Currently, WANJIA has more than 500 employees in order to store powerful teams in reserve to gradually provide better and sustainable services for clients. WANJIA strives to be a leading fenestration enterprise in China and has achieved the highest Northern American Standard, European Standard and Australian Standard, also additional including Energy Star, CSA certification, CE certification, ISO certification and more.

CONTENTS IRON GATE/DOOR

1.Production Process of Iron Door	01
2.Wrought Iron Door	05
3.Iron Interior Door	11
4.Iron Gate	17
5.Color / Glass	21
6 Handlo / Lock	22

PRODUCTION PROCESS OF IRON DOOR






EXQUISITELY CRAFTING EACH DETAIL TO FORGE AN EXCEPTIONAL IRON DOOR.















Wrought Iron Door



Parts





Outer frame: 50*100mm,50*150mm,60*120mm galvanized square tubing/customized dimension Door frame: 150*50mm, 120*50mm galvanized square tubing with high temperature/customized dimension

Profile thickness:2.5/3.0mm

Door sash thickness:40mm/50mm/65mm(thermal-break door)

Door frame thickness:25mm/30mm/40mm/50mm/65mm with sealing strips, and the width can be customized according to the wall thickness.

Wrought iron scroll: 14*14mm/16*16mm solid steel/custom size

Grille: 16*16mm/20*10mm solid steel/custom size

Door trim molding: no/ single wrapping

Restricted size: single door sash, width ranging from 650mm to 1200mm, height up to 4500mm.

Frame width ranging from 250mm to 3500mm, height up to 5500mm.

Craftsmanship: customize according to styles

Glass: customizable

Rust prevention process: galvanized tubing with high heat+galvanized iron treatment for wrought

iron door pattern decorations

Painting process :fluorocarbon painting series. With 1 layer primer+ high heat galvanized coating+ 2

to 3 layers finish coating

Color: customizable Lock set: custom

Lock body: mechanical lock body/magnetic lock body/ball catch lock

Hinge: wrought iron welded hinge


Door threshold: without door sill/ the threshold with seven-character opening inward or outward Optical hardware/accessories: weatherstrip at the door bottom/ball catch door hardware


Door opening method: open inward/outward

Installation method: expansion screw bolt/welded corner brackets/screws for fixing wooden frame

















Builder Solution

































Iron Interior Door



Parts





Outer frame: 50*100mm,50*150mm,60*120mm galvanized square tubing/customized dimension

Door frame: 150*50mm, 120*50mm galvanized square tubing with high temperature/customized dimension

Profile thickness: 2.5/3.0mm

Door sash thickness:40mm/50mm/65mm(thermal-break door)

Door frame thickness:25mm/30mm/40mm/50mm/65mm with sealing strips, and the width can be customized

according to the wall thickness.

Wrought iron scroll: 14*14mm/16*16mm solid steel/custom size

Grille: 16*16mm/20*10mm solid steel/custom size

Door trim molding: no/ single wrapping

Restricted size: single door sash, width ranging from 650mm to 1200mm, height up to 4500mm. Frame width ranging

from 250mm to 3500mm, height up to 5500mm. Craftsmanship: customize according to styles

Glass: customizable

Rust prevention process: galvanized tubing with high heat+galvanized iron treatment for wrought iron door pattern

decorations

Painting process :fluorocarbon painting series. With 1 layer primer+ high heat galvanized coating+ 2 to 3 layers finish

coating

Color: customizable Lock set: custom


Lock body: mechanical lock body/magnetic lock body/ball catch lock

Hinge: wrought iron welded hinge

Door threshold: without door sill/ the threshold with seven-character opening inward or outward Optical hardware/accessories: weatherstrip at the door bottom/ball catch door hardware

Door opening method: open inward/outward

Installation method: expansion screw bolt/welded corner brackets/screws for fixing wooden frame






Builder Solution





Builder Solution

























Iron Gate



Parts













Outer frame: 50*50mm,60*60mm,60*120mm galvanized square tubing/customized dimension

Profile thickness: 2.0mm/2.3mm

Door sash thickness: 40mm/50mm/60mm

Wrought iron scroll: solid steel with customized size

Grille: solid steel with customized size

Iron plate: 3mm/4mm thickness

Door trim molding: no

Restricted size: single door sash 650mm-4500mm in width, and height within 3500mm

Craftsmanship: customize according to styles

Glass: customizable

Rust prevention process: galvanized tubing with high heat + immersion in galvanizing tank

treatment with high temperature

Painting process :fluorocarbon painting series. With 1 layer primer+ high heat galvanized coating+

2 layers finish coating

Color: customizable

Lock set: custom locks/ without locks

Lock body: mechanical lock body/ without lock


Hinge: wrought iron welded hinge

Door threshold: no

Door opening method: open inward or outward/slide

Installation method: expansion screw bolt/welded corner brackets/screws for fixing wooden

frame


























Color



Glass Type



Glass Style



Clear Ripple Glass Granite Textured Glass

Rain Glas


Nashii Clear Patterned

Fluted Glass

Frosted Glass



Large Handles



Entry Door Locks



Interior Door Locks

















buildersolutionus.com